

No Fuss. No Truss.



Mobile video indoor / outdoor display systems that are easy to place and easy to operate.



Caines & Associates
Visual Display • Creative

Model	Pro 16
Pitch	16mm physical 8mm virtual
Display Resolution	192 (w) x 112 (h) Physical 384 (w) x 224 (h) Virtual
Dimensions (w x h)	3208mm x 1928mm (126.3" x 75.91")
Surface	8.19 ² (99 ft. ²)
Aspect Ratio	16:9
LED Specifications	CREE 2R, 1G, 1B
Video Processing	Rackmount Elite p2100



San Ramon, CA (U.S.A.) • Phone: +1.925.215.1886 • <http://www.candassoc.com>



Caines & Associates
Visual Display • Creative

Sales Agent:
Chad Caines
San Ramon, CA.
925.215.1886

Features & Specifications:

<p>LED</p>  <p>DISPLAY</p>	<table border="1"> <tr><td>Type</td></tr> <tr><td>Pitch</td></tr> <tr><td>Display Resolution (Physical / Virtual)</td></tr> <tr><td>Dimensions (W x H)</td></tr> <tr><td>Surface</td></tr> <tr><td>Aspect Ratio</td></tr> <tr><td>Video Processing</td></tr> <tr><td>Content Creation Sources</td></tr> <tr><td>LED Specifications</td></tr> </table>	Type	Pitch	Display Resolution (Physical / Virtual)	Dimensions (W x H)	Surface	Aspect Ratio	Video Processing	Content Creation Sources	LED Specifications	<table border="1"> <tr><td>4x2 APCUS-Pro16</td></tr> <tr><td>P16v8 mm</td></tr> <tr><td>192 (w) x 112 (h) Physical</td></tr> <tr><td>384 (w) x 224 (h) Virtual</td></tr> <tr><td>3208 mm x 1928 mm (126.3" x 75.91")</td></tr> <tr><td>6.19m² (99 ft²)</td></tr> <tr><td>16:9</td></tr> <tr><td>Rack-mount APCUS-Elite p2100</td></tr> <tr><td>X20/SCALA (Optional)</td></tr> <tr><td>CREE 2R, 1G, 1B</td></tr> </table>	4x2 APCUS-Pro16	P16v8 mm	192 (w) x 112 (h) Physical	384 (w) x 224 (h) Virtual	3208 mm x 1928 mm (126.3" x 75.91")	6.19m ² (99 ft ²)	16:9	Rack-mount APCUS-Elite p2100	X20/SCALA (Optional)	CREE 2R, 1G, 1B
Type																					
Pitch																					
Display Resolution (Physical / Virtual)																					
Dimensions (W x H)																					
Surface																					
Aspect Ratio																					
Video Processing																					
Content Creation Sources																					
LED Specifications																					
4x2 APCUS-Pro16																					
P16v8 mm																					
192 (w) x 112 (h) Physical																					
384 (w) x 224 (h) Virtual																					
3208 mm x 1928 mm (126.3" x 75.91")																					
6.19m ² (99 ft ²)																					
16:9																					
Rack-mount APCUS-Elite p2100																					
X20/SCALA (Optional)																					
CREE 2R, 1G, 1B																					
<p>TRAILER SYSTEM</p>	<table border="1"> <tr><td>Total Weight</td></tr> <tr><td>Dimensions (W x H x D)</td></tr> <tr><td>Safety Travelling Speed</td></tr> </table>	Total Weight	Dimensions (W x H x D)	Safety Travelling Speed	<table border="1"> <tr><td>2041 kg (4500 lb)</td></tr> <tr><td>3200mm x 2794mm x 2032mm (126" x 110" x 80")</td></tr> <tr><td>88.51 km/h (55 mph)</td></tr> </table>	2041 kg (4500 lb)	3200mm x 2794mm x 2032mm (126" x 110" x 80")	88.51 km/h (55 mph)													
Total Weight																					
Dimensions (W x H x D)																					
Safety Travelling Speed																					
2041 kg (4500 lb)																					
3200mm x 2794mm x 2032mm (126" x 110" x 80")																					
88.51 km/h (55 mph)																					
<p>TRAILER AND LIFT</p>	<table border="1"> <tr><td>Hydraulic Mast</td></tr> <tr><td>Mast Raise</td></tr> <tr><td>Display Rotation</td></tr> <tr><td>Wind Load</td></tr> <tr><td>Tow Bar</td></tr> </table>	Hydraulic Mast	Mast Raise	Display Rotation	Wind Load	Tow Bar	<table border="1"> <tr><td>Heavy Duty Piston & Ram</td></tr> <tr><td>Bottom of Display 2.1 m, (7.0 ft) from the ground</td></tr> <tr><td>360°</td></tr> <tr><td>72.42 km/h, 45 mph</td></tr> <tr><td>Removable (patented)</td></tr> </table>	Heavy Duty Piston & Ram	Bottom of Display 2.1 m, (7.0 ft) from the ground	360°	72.42 km/h, 45 mph	Removable (patented)									
Hydraulic Mast																					
Mast Raise																					
Display Rotation																					
Wind Load																					
Tow Bar																					
Heavy Duty Piston & Ram																					
Bottom of Display 2.1 m, (7.0 ft) from the ground																					
360°																					
72.42 km/h, 45 mph																					
Removable (patented)																					
<p>EQUIPMENT RACK</p>	<table border="1"> <tr><td>Dimensions</td></tr> <tr><td>Case</td></tr> <tr><td>CPU</td></tr> <tr><td>Keyboard & LCD</td></tr> <tr><td>Scaler (Optional)</td></tr> <tr><td>Power Distribution Center</td></tr> <tr><td>Shock Resistant</td></tr> </table>	Dimensions	Case	CPU	Keyboard & LCD	Scaler (Optional)	Power Distribution Center	Shock Resistant	<table border="1"> <tr><td>12 U Rack System</td></tr> <tr><td>Weather Resistant</td></tr> <tr><td>APCUS-Elite r2100</td></tr> <tr><td>1 U, 15" LCD, Keyboard/touchpad</td></tr> <tr><td>APCUS-Image Pro i2100</td></tr> <tr><td>Junction Box – PDC-4</td></tr> <tr><td>GForce-2100</td></tr> </table>	12 U Rack System	Weather Resistant	APCUS-Elite r2100	1 U, 15" LCD, Keyboard/touchpad	APCUS-Image Pro i2100	Junction Box – PDC-4	GForce-2100					
Dimensions																					
Case																					
CPU																					
Keyboard & LCD																					
Scaler (Optional)																					
Power Distribution Center																					
Shock Resistant																					
12 U Rack System																					
Weather Resistant																					
APCUS-Elite r2100																					
1 U, 15" LCD, Keyboard/touchpad																					
APCUS-Image Pro i2100																					
Junction Box – PDC-4																					
GForce-2100																					
<p>ELECTRICAL</p> 	<table border="1"> <tr><td>Alternating Current – AC</td></tr> <tr><td>Generator</td></tr> <tr><td>Noise Level</td></tr> <tr><td>Exhaust System</td></tr> <tr><td>Start</td></tr> <tr><td>Run Time</td></tr> <tr><td>Fuel Capacity (gasoline)</td></tr> </table>	Alternating Current – AC	Generator	Noise Level	Exhaust System	Start	Run Time	Fuel Capacity (gasoline)	<table border="1"> <tr><td>240v, 30amp</td></tr> <tr><td>10,000W Peak, Gentron-Pro</td></tr> <tr><td><72 dB at 6m (20 ft)</td></tr> <tr><td>Directional down flow</td></tr> <tr><td>Electric Key Start</td></tr> <tr><td>8.5 hrs @ ½ load</td></tr> <tr><td>All Steel 6.6 gallons</td></tr> </table>	240v, 30amp	10,000W Peak, Gentron-Pro	<72 dB at 6m (20 ft)	Directional down flow	Electric Key Start	8.5 hrs @ ½ load	All Steel 6.6 gallons					
Alternating Current – AC																					
Generator																					
Noise Level																					
Exhaust System																					
Start																					
Run Time																					
Fuel Capacity (gasoline)																					
240v, 30amp																					
10,000W Peak, Gentron-Pro																					
<72 dB at 6m (20 ft)																					
Directional down flow																					
Electric Key Start																					
8.5 hrs @ ½ load																					
All Steel 6.6 gallons																					
<p>PACKAGING</p>	<table border="1"> <tr><td>Manuals</td></tr> <tr><td>Certificates</td></tr> <tr><td>LED Display Cover</td></tr> <tr><td>Rear Service Panels</td></tr> <tr><td>Spare Tire</td></tr> <tr><td>Generator Cover</td></tr> <tr><td>Utility Box</td></tr> <tr><td>Clearance Markers</td></tr> </table>	Manuals	Certificates	LED Display Cover	Rear Service Panels	Spare Tire	Generator Cover	Utility Box	Clearance Markers	<table border="1"> <tr><td>Installation & Troubleshooting</td></tr> <tr><td>CE, UL P/S, DOT rated trailer</td></tr> <tr><td>Protective Acrylic Ad Covers</td></tr> <tr><td>Easy Access & Weatherproof</td></tr> <tr><td>Full size trailer mount</td></tr> <tr><td>Protective Sheet metal & lock</td></tr> <tr><td>Protective Sheet metal & lock</td></tr> <tr><td>LED 6' x 2', Red & Amber</td></tr> </table>	Installation & Troubleshooting	CE, UL P/S, DOT rated trailer	Protective Acrylic Ad Covers	Easy Access & Weatherproof	Full size trailer mount	Protective Sheet metal & lock	Protective Sheet metal & lock	LED 6' x 2', Red & Amber			
Manuals																					
Certificates																					
LED Display Cover																					
Rear Service Panels																					
Spare Tire																					
Generator Cover																					
Utility Box																					
Clearance Markers																					
Installation & Troubleshooting																					
CE, UL P/S, DOT rated trailer																					
Protective Acrylic Ad Covers																					
Easy Access & Weatherproof																					
Full size trailer mount																					
Protective Sheet metal & lock																					
Protective Sheet metal & lock																					
LED 6' x 2', Red & Amber																					
<p>PRICING</p>	<table border="1"> <tr><td>Dealer Standard Loaded</td></tr> <tr><td>Optional – 3rd Party Software</td></tr> <tr><td>Optional – APCUS Image Pro</td></tr> </table>	Dealer Standard Loaded	Optional – 3 rd Party Software	Optional – APCUS Image Pro	<table border="1"> <tr><td>\$55,000. FOB Atlanta, GA. USA</td></tr> <tr><td>\$5,000 to \$10,000</td></tr> <tr><td>\$5000.</td></tr> </table>	\$55,000. FOB Atlanta, GA. USA	\$5,000 to \$10,000	\$5000.													
Dealer Standard Loaded																					
Optional – 3 rd Party Software																					
Optional – APCUS Image Pro																					
\$55,000. FOB Atlanta, GA. USA																					
\$5,000 to \$10,000																					
\$5000.																					
<p>MAINTAINENCE</p>	<table border="1"> <tr><td>Standard</td></tr> <tr><td>Optional</td></tr> </table>	Standard	Optional	<table border="1"> <tr><td>Offsite technical training & troubleshooting</td></tr> <tr><td>Onsite technical training & troubleshooting per visit</td></tr> </table>	Offsite technical training & troubleshooting	Onsite technical training & troubleshooting per visit															
Standard																					
Optional																					
Offsite technical training & troubleshooting																					
Onsite technical training & troubleshooting per visit																					
<p>WARRANTY</p>	<table border="1"> <tr><td>Standard</td></tr> <tr><td>Optional</td></tr> <tr><td>Optional</td></tr> <tr><td>Optional</td></tr> <tr><td>Optional</td></tr> </table>	Standard	Optional	Optional	Optional	Optional	<table border="1"> <tr><td>1 year parts</td></tr> <tr><td>2 year parts</td></tr> <tr><td>3 year parts</td></tr> <tr><td>4 year parts</td></tr> <tr><td>5 year parts</td></tr> </table>	1 year parts	2 year parts	3 year parts	4 year parts	5 year parts									
Standard																					
Optional																					
Optional																					
Optional																					
Optional																					
1 year parts																					
2 year parts																					
3 year parts																					
4 year parts																					
5 year parts																					

<http://www.candassoc.com>

Technical specifications are subject to change without notice.
Please contact your sales agent for updated technical data.