



Caines & Associates
Visual Display • Creative

Sales Agent:
Chad Caines
San Ramon, CA.
925.215.1886

Outdoor Visual Display Modules

	IV16	IV20	IV32
Pitch	8mm	10mm	16mm
Pixel Density	2,400/Tile (40x60)	1,536/Tile (32x48)	600/Tile (20x30)
Brightness	5500-6500NIT	5500-6500NIT	5500-6500NIT
LED Configuration	2R, 1G, 1B	2R, 1G, 1B	4R, 2G, 2B
Viewing Angle			
Horizontal	120°	120°	120°
Vertical	60°	60°	60°
Color Temperature	3200K-9300K flexibl	3200K-9300K flexibl	3200K-9300K flexib
Life span <i>(Fully white-half brightness)</i>	50,000h	50,000h	50,000h
Power Consumption			
Maximum	600W	600W	600W
Average	180W	200W	200W
Weight/Tile	70.4lbs	70.4lbs	70.4lbs
Color Processing	16bit	16bit	16bit
Grayscale	10bit	10bit	10bit
Colors	280 trillion	280 trillion	280 trillion
Frame Rate	> =60HZ	> =60HZ	> =60HZ
Refresh Rate	> =1000HZ	> =1000HZ	> =1000HZ
Temperature	-20 - 120 F	-20 - 120 F	-20 - 120 F
Humidity	10% to 99%	10% to 99%	10% to 99%
Certified	UL CE FCC IP65	UL CE FCC IP65	UL CE FCC IP65
Cooling	Circulating air	Circulating air	Circulating air
Control System	PC	PC	PC



- Modular design
- Air cooled

<http://www.candassoc.com>

Technical specifications are subject to change without notice.
Please contact your sales agent for updated technical data.